Линия автоматической очистки картофеля (Италия).

Производительность версии с одной очистительной машиной 600 кг/ч
Производительность версии с двумя очистительными машинами 1200 кг/ч

Поточное решение задач при минимальном количестве людей.
Оборудование премиум класса производства Италия.

Стоимость линии 26 470 ЕВРО

Стоимость пусконаладочных работ обсуждается дополнительно.

Цены даются на условиях франко-завод (EXW), Италия

ATTN: MR. VLADIMIR ATANASOV

MONO-DIRECTIONAL PIONEER SYSTEM
POTATO PEELING LINE



The **PIONEER INTEGRATED SYSTEM** features a high productivity combined with a considerable ease of handling. This System allows the processing of big amounts of potatoes, reducing manual work, downtimes and space requirements, and resulting in a quick and rational work flow.

Technical features

Width: 3700 mm
Depth: 1080 mm
Height: 2350 mm
Capacity: 600 kg/h
Voltage: 3~230/400V 50Hz

COMPOSITION OF THE LINE

MONO-DIRECTIONAL ELEVATOR BY ENDLESS SCREW

- Pre-washing and loading vat having a capacity of 200 kg and equipped with: overflow; cold water inlet (diameter: 3/4"); drain (diameter: 2") with ball valve.
- Powered by a gearmotor (1,5 kW).
- Made of AISI 304 stainless steel.
- 24V control panel equipped with: power light; loading timer; peeling timer, elevator starting button; peeler starting button; emergency-stop button; cycle starting and outfeed opening/closing selector.
- Manufactured in accordance with the EN 60 335-1 and the EN 60 335-2-64 Standards.
- Provided with the CE Marking.

How it works

The screw elevator draws potatoes from the hopper and feeds the potato peeler. The batch of product to be processed and the preferred peeling times can be set on the control panel located on the elevator.

CODE: 83203000

LIST PRICE	QTY.		
EUR 26.470,00	1		
Packing charges	1		EUR 480,00